



The RT230H is RTscan's new generation OEM 2D fixed mount barcode scanner, with fixed mount and compact design, its suitable for all kinds of Kiosk, ATM, ticket terminal, medical device for embedded use.

Supports sense mode(detect and read bar codes automatically), continuous mode and trigger mode, with interface USB-HID, USB-Virtual Com, and RS232 .

Readable most 1D barcode and 2D barcode such as QR code, PDF417 code, Data Matrix, Aztec Code...and also with high performance for reading codes from phone screen.



- Small
- Fixed Mount
- 1D / 2D / QR / PDF417
- USB / RS232 interface
- Read from Paper / Phone screen

Features:

- Fixed mount barcode scanner compact design
- With Infrared sensor, more accurate and durable
- USB/ RS232 interface
- Readable PDF417 in some ID/Passport
- Supports most 1D and 2D bar codes, Aztec, QR code, PDF417.
- Readable either from LCD screen or from paper





Specification:

		hanical		
I\ /	വെ	nan	102	ı
1 V		Iui	ILCU	

Dimensions (DxWxH) 60mm*45mm*22.5mm

Weight 100 g

Electrical

Input Voltage 5 VDC **Operating Power** 210mA-5V

Red LED 625±10 nm Light source

Interfaces RS232, USB (HID-KBW), USB-VCOM (different interface matches corresponding

cable, the cable is fixed on the scanner and it is not changeable.)

Environmental

Operating Temperature -20°C to 50°C Storage Temperature -40°C to 80°C

Humidity 5% to 95% relative humidity, non-condensing

Ambient light 0 to 100,000 lux

Scan Performance

Scan Pattern Area Imaging

Image sensor 640*480 pixels CMOS, resoltion≥5mil

Field of view Horizontal 44°, Vertical 33.2° Symbol Contrast ≥30% reflectance difference

Pitch, Skew, rotate ±40°, ±40°, 360°

Decode Capability 1D: Code128, UCC/EAN-128, AIM-128, EAN-8, EAN-13, ISBN/ISSN,

> UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11,

Plessey, MSI-Plessey, GS1-DataBarTM(RSS), (RSS-14, RSS-Limited, RSS-Expand)

2D: PDF417, QR Code (QR1/2, Micro), Data Matrix (ECC200, ECC000,

050, 080, 100, 140)

Decode range

Code 39 (5mil) 35mm-160mm EAN-13 (13mil) 60mm-345mm PDF417 (6.67mil) 40mm-115mm QR code(13mil) 40mm-150mm Data Matrix (10mil) 35mm-110mm

Performance may be impacted by bar code quality and environment conditions.



mounting screw holes